


TECHNICAL DATA		50 Hz	60 Hz
• Power (with ATEX certified vacuum unit)	kW-HP	2,2 - 3	2,55 - 3,4
• Input voltages ¹⁾ Current settings available	V A	400Y 4,55Y ²⁾ 230D 7,9D	460Y 4,5Y ---
• Electrical cable length Electrical plug		6 meters Not supplied	
• ATEX mark		 II 3D - Ex c t IIIC T125°C Dc	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP 65 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	2.500 2.200	3.000 2.600
• Maximum air flow	l/min - m ³ /h	3.500 - 210	4.166 - 250
• Acoustic level ^{d)}	dB (A)	69	70
• Dust Bin: capacity	l	25	
• Diameters: material inlet	mm	50	
• Dimensions: L x W (W.090) x H Weight	mm kg	830 x 460 (460) x 1.000 39	
• Packing size ⁵⁾ : L x W (W.090) x H Weight	mm kg	871 x 671 (671) x 1.200 44	
• Primary filter		Star filter	
Surface area Diameter	cm ² - m ² mm	7.000 - 0,7 360	
Dust Class ⁶⁾ ^{e)} Media ⁷⁾		M Antistatic polyester	
Filter cleaning ⁸⁾		Ergonomic manual shaker	
• Automatic filter cleaning - Optional		---	
Surface area Nominal output	cm ² - m ² m ³ /h	---	
Dust Class ^{e)} Media		---	
Compressed air consumption pressure	nl/min bar	---	
• Upstream absolute filter - Optional		HEPA 14	
Surface area Nominal output	cm ² - m ² m ³ /h	17.000 - 1,7 ---	
Dust Class ^{f)} Media		H14 Glass fibre	
Efficiency M.P.P.S. ^{f)} (with 0,18 µm particles)		99,995%	

KH1636.022


Three Phase
For ATEX zone 22
IP65
In presence of conductive dust

¹⁾ Other input voltages upon request

²⁾ Default factory setting

³⁾ Maximum vacuum in continuous run

⁴⁾ ---

⁵⁾ Standard packing size

⁶⁾ PTFE coated antistatic star filter available upon request

⁷⁾ Other materials available according to the material to be vacuumed

⁸⁾ ---

⁹⁾ AISI 316L cleaned welding and inner mirror polished

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

BASIC VERSION PRICES		£
• KH1636.022	25 litres three phase vacuum dust collector - IP65 - ATEX zone 22	2.639,00
OPTIONS		£
• 001	AISI 304 stainless steel dust bin	included
•	AISI 316L stainless steel dust bin, "pharma finishing" ⁹⁾	+ 697,00
• 003	AISI 304 stainless steel completely made	+ 306,00
•	AISI 316L stainless steel completely made, "pharma finishing" ⁹⁾	+ 1.005,00
• 005	Upstream absolute filter (HEPA)	+ 159,00
•	Overheating safety relief valve	+ 120,00
•	Silencer for painted version	included
•	Silencer for stainless steel version (.003)	included
• 090	On/off switch with thermal protection	+ 153,00
• 100	Fitted with single-phase vacuum unit	+ 253,00

THE ABOVE MENTIONED PRICES DO NOT INCLUDE ANY ACCESSORIES. For an effective and proper use according to your application requirements, please see our AP price list.

Versions available: L-M-H filtration (for hazardous powders vacuuming) certification