

KB5P



- GENERAL FEATURES**
- Overheating safety relief valve
 - Vacuumeter upon request
 - L-M-H filtration for hazardous dust vacuuming upon request

MACHINE




KB5P 5,5 kW, 90 l capacity, blue RAL 5012 painted, 460 mm diameter three phase industrial vacuum cleaner

KB5P/50 5,5 kW, 50 l capacity, blue RAL 5012 painted, 460 mm diameter three phase industrial vacuum cleaner

TECHNICAL DATA

		50 Hz	60 Hz
Power	kW - HP	5,5 - 7,4	6,6 - 8,8
Input voltages Y ¹⁾	V	400	380
Current Y	A	11	12,1
Input voltages D ¹⁾	V	230	220
Current D	A	19	21
Electric protection ²⁾		IP55	
Default factory setting	l lb	400 50	
Electrical cable:			
type		4G2,5 H07RN-F	
length	m	9	
plug		16 A with phase inverter - 4 poles	
Insulation class ³⁾		F	
Energetic class ⁴⁾		IE1	
Maximum vacuum	mmH ₂ O	2.550	3.150
	mbar	255	315
Nominal vacuum ⁵⁾	mmH ₂ O	2.500	2.500
	mbar	250	250
Maximum air flow	l/min	9.100	10.500
	m ³ /h	546	630
Acoustic level ⁶⁾	dB (A)	74	75
Environmental working temperature	°C	5 + 40	
Dust bin capacity	l	90 - 50	
Wheels material		Rubber	
Weight	kg	149	
Packing weight	kg	164	
Dimensions - L x W x H (D08)	90 L 50 L	990 x 650 x 1.440 (1.740) 990 x 650 x 1.220 (1.520)	
Standard packing size - L x W x H (D08)	90 L 50 L	1.140 x 730 x 1.610 (1.850) 1.140 x 730 x 1.610 (1.630)	
Diameters:			
material inlet	mm	70	
air exhaust	mm	100	
wheels: chassis	mm	150 - 200	
wheels: bin	mm	60	

FILTRATION DATA

	Default primary star filter		
	Surface area	cm ² - m ²	19.500 - 1,95
	Diameter	mm	460
	Dust Class ^{a)} Media ^{b)}		L Polyester
	Filter cleaning		Manual filter shaker
	Optional primary filter - cartridges kit - Variant 008		
	Surface area Diameter	cm ² - m ² mm	56.400 - 5,64 400
	Dust Class ^{a)} Media		M Antistatic polyester
	Compressed air consumption pressure	nl/min bar	48 4 + 6
	Filter cleaning		Automatic cleaning system
	Upstream absolute filter - Variant 005		
	Surface area	cm ² - m ²	52.000 - 5,2
	Media		Glass fibre
	Dust Class ^{b)}		H14
	Efficiency M.P.P.S. ^{1)c)}		99,995%

Normatives: a) IEC60529; b) IEC60085; c) IEC60334-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

- Notes:
- ¹⁾ Other input voltages upon request
 - ²⁾ Maximum vacuum in continuous run
 - ³⁾ Other materials available according to the material to be vacuumed
 - ⁴⁾ With 0,15 µm particles

OUTFITS		90 l - E	50 l - E
ACD	Appliance for combustible dust vacuuming according to IEC 60335-2-69 ED6 - 2020	R	R
001	AISI 304 stainless steel dust bin	R	R
002	AISI 304 stainless steel dust bin and filtering chamber	R	R
003	Entirely made out of AISI 304 stainless steel	R	R
004	Liquids bin level monitoring system switch off	R	R
005	Upstream absolute filter (HEPA)	R	R
006	Electric filter shaker with push-button	R	R
006A	Automatic electric filter shaker	R	R
008	Automatic reverse jet cartridge filtering system	X	X
008S	Automatic reverse jet cartridge filtering system - version: AISI 304 stainless steel	X	X
075	Bin overfilling machine switch off	R	R
104	Remote on/off switch arrangement through dry contact onto processing machine electric control panel	R	R
120	M dust class primary filter	R	R
320	Vulkolon wheels	R	R
403	Disposal bag vacuum balance system for dust collection directly into plastic bags	R	R
800	Material inlet fitted on cartor wheels side	X	X
821	Air exhaust hose fitting	R	R
MARKWH	Mark proof wheels with bearings	R	R