



info@kevac.eu
www.kevac.eu



K11P/78



GENERAL FEATURES

- Overheating safety relief valve
- Mark proof wheels with bearings
- L-M-H filtration for hazardous dust vacuuming upon request




MACHINE

K11P/78 11 kW, 175 l capacity, blue RAL 5012 painted, 560 mm diameter three phase industrial vacuum cleaner

K11P/78/90 11 kW, 90 l capacity, blue RAL 5012 painted, 560 mm diameter three phase industrial vacuum cleaner

TECHNICAL DATA		50 Hz	60 Hz
Power	KW - HP	11 - 14,7	13 - 17,4
Input voltages Y ¹⁾	V	600 ... 720	660 ... 830
Current Y	A	12,5	12,2
Input voltages D ²⁾	V	345 ... 415	380 ... 480
Current D	A	21,7	21,2
Electric protection ³⁾		IP55	
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G6 H07RN-F	
length	m	9	
plug		32 A with phase inverter - 4 poles	
Insulation class ⁴⁾		F	
Energetic class ⁴⁾		IE3	
Maximum vacuum	mmHg O mbar	5.000 500	5.600 560
Nominal vacuum ²⁾	mmHg O mbar	3.000 300	2.750 275
Maximum air flow	l/min m ³ /h	16.433 986	18.983 1.139
Acoustic level ⁴⁾	dB (A)	78	79
Environmental working temperature	°C	5 + 40	
Dust bin capacity	l	175 - 90	
Wheels material		Polyurethane	
Weight	kg	371	
Packing weight	kg	391	
Dimensions - L x W x H (005 - 008)	175 l 90 l mm	1.720 x 880 x 2.165 (2.365 - 2.220)	
	175 l 90 l mm	1.720 x 880 x 2.050 (2.250 - 2.105)	
Standard packing size - L x W x H (005 - 008)	175 l 90 l mm	1.800 x 950 x 2.305 (2.505 - 2.360)	
	175 l 90 l mm	1.800 x 950 x 2.190 (2.390 - 2.245)	
Diameters:			
material inlet	mm	100	
air exhaust	mm	150	
wheels: chassis	mm	200 - 250	
wheels: bin	mm	100	

FILTRATION DATA

Default primary star filter			
	Surface area	cm ² - m ²	65.000 - 6,5
	Diameter	mm	780
	Dust Class ¹⁾ Media ²⁾		L Polyester
	Filter cleaning		Electric filter shaker with push-button
Optional primary filter - cartridges kit - Variant 008			
	Surface area Diameter	cm ² - m ² mm	126.400 - 12.64 780
	Dust Class ¹⁾ Media		M Antistatic polyester
	Compressed air consumption pressure	nl/min bar	48 4 + 6
	Filter cleaning		Automatic cleaning system
Upstream absolute filter - Variant 005			
	Surface area	cm ² - m ²	130.000 - 13
	Media		Glass fibre
	Dust Class ³⁾		H14
	Efficiency M.P.P.S. ¹⁾⁴⁾		99,995%

Normatives: a) IEC60529; b) IEC60008; c) IEC60314-2-1; d) EN60704-2-1; e) EN60315-2-49; f) EN1822

Note:

¹⁾ Other input voltages upon request

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

⁴⁾ With 0,18 µm particles

OUTFITS	175 l - E	90 l - E
ACD Appliance for combustible dust vacuuming according to IEC 60335-2-69 ED6 - 2020	R	R
001 AISI 304 stainless steel dust bin	R	R
002 AISI 304 stainless steel dust bin and filtering chamber	R	R
003 Entirely made out of AISI 304 stainless steel	R	R
005 Upstream absolute filter (HEPA)	R	R
005SS Upstream absolute filter (HEPA) with M dust class primary filter - version: AISI 304 stainless steel	R	R
006 Electric filter shaker with push-button	I	I
006A Automatic electric filter shaker	R	R
008 Automatic reverse jet cartridge filtering system	R	R
008SS Automatic reverse jet cartridge filtering system - version: AISI 304 stainless steel	R	R
075 Bin overfilling machine switch off	R	R
104 Remote on/off switch arrangement through dry contact onto processing machine electric control panel	R	R
120 M dust class primary filter	R	R
405 Disposal bag vacuum balance system for dust collection directly into plastic bags	R	R
804 Reinforced dust bin	R	R
820 Forklift forklift sockets	R	R
821 Air exhaust hose fitting	R	R