



info@kevac.eu
www.kevac.eu



MACHINES2CLEAN
affordable cleaning machines

KMB3.069



GENERAL FEATURES

• Visual liquid level indicator



MACHINE

KMB3.069	3 kW, blue RAL 5012 painted, 460 mm diameter single phase industrial sumps cleaner
KMB3/120.069	3 kW, blue RAL 5012 painted, 460 mm diameter single phase industrial sumps cleaner

TECHNICAL DATA

		50/60 Hz
Power	kW - HP	3 - 4
Input voltages Y ¹⁾	V	230
Current Y	A	13,5
Electric protection ²⁾		IP43
Default factory setting	V Hz	230 50/60
Electrical cable:		
type		3G1,5 H07RN-F
length	m	9
plug		Schuko
Insulation class ³⁾		F
Maximum vacuum	mmHg	2.100
	mbar	210
Maximum air flow	l/min	8.667
	m³/h	520
Acoustic level ⁴⁾	dB (A)	73
Environmental working temperature	°C	5 ÷ 40
Dust bin capacity	l	90 - 120
Wheels material		Rubber
Weight	kg	65
Packing weight	kg	75
Dimensions - L x W x H	90 l mm	705 x 603 x 1.195
	120 l mm	705 x 603 x 1.410
Standard packing size - L x W x H	90 l mm	740 x 730 x 1.610
	120 l mm	740 x 730 x 1.610
Diameters:		
material inlet	mm	70
wheels: rear front	mm	150 - 200
wheels: bin	mm	60

FILTRATION DATA

• Default primary filter		Cartridge filters
Surface area	cm² - m²	21.000 - 2,1
Diameter	mm	460
Dust Class ^{a)} Media ^{b)}		... Polyester - oil & water repellent

EXPPELLING SYSTEM

Pump power	kW - HP	0,75 - 1,02
Pump capacity	l/min	220
Hose length inner diameter	m mm	3 m 30 mm

SWARF BASKET

Capacity	l	40
Diameter	basket	450
	holes	2

Normatives: a) IEC60529; b) IEC60085; c) EN60704-2-1; d) EN60335-2-69;

Notes:

¹⁾ Other input voltages upon request.

²⁾ Maximum vacuum in continuous run.

³⁾ Other materials available according to the material to be vacuumed.

OUTFITS

	90 l - €	120 l - €
001	AISI 304 stainless steel dust bin	R R
002	AISI 304 stainless steel dust bin and filtering chamber	R R
003	Entirely made out of AISI 304 stainless steel	R R
004	Liquids bin level monitoring system switch off	R R
320	Vulkolan wheels	R R
MARKWH	Mark proof wheels with bearings	R R