



info@kevac.eu
www.kevac.eu



MACHINES2CLEAN
affordable cleaning machines

KMOIL230



GENERAL FEATURES

- Visual liquid level indicator
- Draining valve and expelling system

MACHINE

KMOIL230 3 kW, blue RAL 5012 painted, single phase industrial sumps cleaner

TECHNICAL DATA		50/60 Hz
Power	kW - HP	3 - 4
Input voltages Y ¹⁾	V	230
Current Y	A	13,5
Electric protection ²⁾		IP43
Default factory setting	V Hz	230 50/60
Electrical cable:		
type		3G1,5 H07RN-F
length	m	9
plug		Schuko
Insulation class ³⁾		F
Maximum vacuum		
	mmHg	2.100
	mbar	210
Maximum air flow		
	l/min	8.667
	m³/h	520
Acoustic level ⁴⁾	dB (A)	73
Environmental working temperature	°C	5 ± 40
Dust bin capacity	l	200
Wheels material		Polyurethane
Weight	kg	150
Packing weight	kg	165
Dimensions - L x W x H	mm	1.153 x 555 x 1.295
Standard packing size - L x W x H	mm	1.140 x 730 x 1.405
Diameters:		
material inlet	mm	50
wheels: rear front	mm	150 - 150

FILTRATION DATA

* Default primary filter		Cartridge filters
Surface area	cm² - m²	21.000 - 2,1
Diameter	mm	460
Dust Class ⁵⁾ Media ⁶⁾		--- Polyester - oil & water repellent

EXPELLING SYSTEM

Pump power	kW - HP	0,33 0,71
Pump capacity	l/min	200
Hose length inner diameter	m mm	3 30

SWARF BASKET

Capacity	l	28
Diameter	basket	360
	holes	2

Normatives: a) IEC60529; b) IEC60008; c) EN60704-2-1; d) EN60335-2-49;

Notes:

¹⁾ Other input voltages upon request.

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

OUTPITS

		€
* 209175	Nylon filter 300 micron - Ø360	8
* 209180	Nylon filter 200 micron - Ø360	8