



info@kevac.eu
www.kevac.eu



MACHINES2CLEAN
affordable cleaning machines

KOIL240



GENERAL FEATURES

- Visual liquid level indicator
- Expelling system



MACHINE

KOIL240 4 kW, l capacity, blue RAL 5012 painted, three phase industrial sumps cleaner

TECHNICAL DATA

		50 Hz	60 Hz
Power	kW - HP	4,0 - 5,4	
Input voltages Y ¹⁾	V	400	
Current Y	A	8,9	
Input voltages D ¹⁾	V	230	
Current D	A	15,4	
Electric protection ²⁾			IP55
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G2,5 H07RN-F	
length	m	9	
plug		16 A with phase inverter - 4 poles	
Insulation class ³⁾		F	
Energetic class ⁴⁾		IE1	
Maximum vacuum	mmHg	3.600	
	mbar	360	
Nominal vacuum ²⁾	mmHg	2.700	
	mbar	270	
Maximum air flow	l/min	5.600	
	m ³ /h	336	
Acoustic level ⁵⁾	dB (A)	75	
Environmental working temperature	°C	5 ± 40	
Tank capacity	l	200	
Wheels material		Polyurethane	
Weight	kg	176	
Packing weight	kg	191	
Dimensions - L x W x H	mm	1.153 x 555 x 1.610	
Standard packing size - L x W x H	mm	1.140 x 730 x 1.720	
Diameters:			
material inlet	mm	50	
air exhaust	mm	100	
wheels	mm	150 - 150	

EXPELLING SYSTEM

	Pump power	kW - HP	0,53 0,71
	Pump capacity	l/min	200
	Hose length inner diameter	m mm	3 30

SWARF BASKET

	Capacity	l	28
	Diameter	basket	360
		holes	2

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1;

Notes:

¹⁾ Other input voltages upon request

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

OUTFITS

		€
209175	Nylon filter 300 micron - Ø360	R
209176	Nylon filter 100 micron - Ø360	R
209180	Nylon filter 200 micron - Ø360	R
821	Air exhaust hose fitting	R