



info@kevac.eu
www.kevac.eu



MACHINES2CLEAN
affordable cleaning machines

KOIL455T



GENERAL FEATURES

- Visual liquid level indicator
- Expelling system

MACHINE

KOIL455T 5,5 kW, l capacity, blue RAL 5012 painted, three phase industrial sumps cleaner

TECHNICAL DATA		50 Hz	60
Power	kW - HP	5,5 - 7,4	6,6
Input voltages Y ¹⁾	V	400	3
Current Y	A	11	12
Input voltages D ¹⁾	V	230	2
Current D	A	19	2
Electric protection ⁴⁾		IP55	
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G2,5 H07RN-F	
length	m	9	
plug		16 A with phase inverter - 4 poles	
Insulation class ³⁾		F	
Energetic class ⁴⁾		IE1	
Maximum vacuum	mmHg	5.100	5.1
	mbar	510	51
Nominal vacuum ²⁾	mmHg	4.000	4.1
	mbar	400	41
Maximum air flow	l/min	5.600	6.1
	m ³ /h	336	4
Acoustic level ⁵⁾	dB (A)	75	7
Environmental working temperature	°C	5 ± 40	
Tank capacity	l	400	
Wheels material		Polyurethane	
Weight	kg	273	
Packing weight	kg	293	
Dimensions - L x W x H	mm	1.407 x 660 x 1.927	
Standard packing size - L x W x H	mm	1.600 x 800 x 2.037	
Diameters:			
material inlet	mm	50	
air exhaust	mm	100	
wheels	mm	200 - 200	

EXPELLING SYSTEM

	Pump power	kW - HP	0,78 1,05
	Pump capacity	l/min	220
	Hose length inner diameter	m mm	3 30

SWARF BASKET

	Capacity		l	60
	Diameter	basket	mm	460
		holes	mm	2

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1;

Notes:

¹⁾ Other input voltages upon request

²⁾ Maximum vacuum in continuous run

³⁾ Other materials available according to the material to be vacuumed

OUTFITS

		£	R
209174	Nylon filter 300 micron - Ø460		R
209181	Nylon filter 200 micron - Ø460		R
821	Air exhaust hose fitting		R