

K9/78M.022B

3~ M Ex IP55

ATEX ZONE 22

NO CONDUCTIVE DUST



GENERAL FEATURES

- Overheating safety relief valve
- Antistatic wheels
- H filtration for hazardous dust vacuuming upon request

MACHINE

K9/78M.022B 9,2 kW, 175 l capacity, blue RAL 5012 painted, 560 mm diameter three phase industrial vacuum cleaner

K9/78/90M.022B 9,2 kW, 90 l capacity, blue RAL 5012 painted, 560 mm diameter three phase industrial vacuum cleaner

TECHNICAL DATA

		50 Hz	
Power	kW · HP	9,2 · 12,5	
Input voltages Y ¹⁾	V	600 ... 720	
Current Y	A	10,3	
Input voltages D ¹⁾	V	400	
Current D	A	17,8	
Electric protection ²⁾			IP55
Default factory setting	V Hz	400 50	
Electrical cable:			
type		4G6 H07RN-F	
length	m	9 m	
plug		Not supplied	
Insulation class ³⁾			F
Energetic class ¹⁾			IE2
ATEX Mark ⁴⁾			II 3D - Ex h I c IIB T 135°C Dc
Maximum vacuum	mmHg	4.300	
	mbar	430	
Nominal vacuum ²⁾	mmHg	3.000	
	mbar	300	
Maximum air flow	l/min	13.683	
	m³/h	821	
Acoustic level ⁵⁾	dB (A)	78	
Environmental working temperature	°C	5 ÷ 40	
Dust bin capacity	l	175 - 90	
Wheels material		Polyurethane	
Weight	kg	385	
Packing weight	kg	405	
Dimensions - L x W x H (005 - 008)	mm	1.720 x 880 x 2.165 (2.365 - 2.220)	
Standard packing size - L x W x H (005 - 008)	mm	1.800 x 950 x 2.305 (2.505 - 2.360)	
Diameters:			
material inlet	mm	100	
air exhaust	mm	150	
wheels: chassis	mm	200 - 250	
wheels: bin	mm	100	

FILTRATION DATA

	Default primary star filter		
	Surface area	cm² · m²	65.000 - 6,5
	Diameter	mm	780
	Dust Class ¹⁾ Media ²⁾		M Antistatic polyester
	Filter cleaning		Electric filter shaker with push-button
	Optional primary filter - cartridges kit - Variant 008		
	Surface area Diameter	cm² · m² mm	126.400 - 12,64 780
	Dust Class ¹⁾ Media		M Antistatic polyester
	Compressed air consumption pressure	nl/min bar	48 4 ÷ 6
	Filter cleaning		Automatic cleaning system
	Upstream absolute filter - Variant 005		
	Surface area	cm² · m²	130.000 - 13
	Media		Glass fibre
	Dust Class ¹⁾		H14
	Efficiency M.P.P.S. ¹⁾ ⁴⁾		99,995%

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) 2014/34/UE; e) EN60704-2-1; f) EN60335-2-69; g) EN1822

Notes:

¹⁾ Other input voltages upon request.²⁾ Maximum vacuum in continuous run.³⁾ Other materials available according to the material to be vacuumed.⁴⁾ With 0,18 µm particles.

OUTFITS

	175 l - E	90 l - E
001	AlSi 304 stainless steel dust bin	R
002	AlSi 304 stainless steel dust bin and filtering chamber	R
003	Entirely made out of AlSi 304 stainless steel	R
005	Upstream absolute filter (HEPA)	R
005SS	Upstream absolute filter (HEPA) with M dust class primary filter - version: AlSi 304 stainless steel	R
006	Electric filter shaker with push-button	I
006A	Automatic electric filter shaker	R
008	Automatic reverse jet cartridge filtering system	R
008SS	Automatic reverse jet cartridge filtering system - version: AlSi 304 stainless steel	R
044	Bin overfilling machine switch off	R
104	Remote on/off switch arrangement through dry contact onto processing machine electric control panel	R
403	Disposal bag vacuum balance system for dust collection directly into plastic bag	R
804	Reinforced dust bin	R
820	Forklift forks sockets	R
821	Air exhaust hose fitting	R

LEGEND:

R = Price upon request

I = Included

X = Not available