

TECHNICAL DATA				50 Hz	60 Hz
• Power	kW - HP			2,2 - 3	2,5 - 3,35
• Input voltages <sup>1)</sup>   Current settings available	V   A			360Y ... 440Y   6Y <sup>2)</sup> 200D ... 240D   10,4D	380Y ... 480Y   6Y 220D ... 275D   10,4D
• Electrical cable length   Electrical plug				6 meters   Not supplied	
• ATEXmark				NO ATEX	
• Electric protection <sup>a)</sup>   Insulation class <sup>b)</sup>   Energetic class <sup>c)</sup>				IP 55   F   IE1	
• Maximum vacuum   Optimum vacuum <sup>3)</sup>	mmH <sub>2</sub> O			3.100   2.200	3.300   2.530
• Maximum air flow	l/min - m <sup>3</sup> /h			5.166 - 310	6.000 - 360
• Acoustic level <sup>d)</sup>	dB (A)			68	72
• Dust Bin: capacity	l			150	
• Diameters: material inlet   wheels <sup>4)</sup> (front - rear)	mm			70   100	
• Dimensions: L x W x H   Weight	mm   kg			646 x 565 x 1.257   61	
• Packing size <sup>5)</sup> : L x W x H   Weight	mm   kg			720 x 720 x 1.400   67	
• Primary filter				Bag filter	
Surface area   Diameter	cm <sup>2</sup> - m <sup>2</sup>   mm			13.000 - 1,3   560	
Dust Class <sup>e)</sup>   Media				Nylon L   Polyester	

<sup>1)</sup> Other input voltages upon request

<sup>2)</sup> Default factory setting

<sup>3)</sup> Maximum vacuum in continuous run

<sup>4)</sup> Marks proof wheels

<sup>5)</sup> Standard packing size



Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69

BASIC VERSION PRICES			£
• KR2256	150 litres three phase vacuum waste collector - Painted		2.024,00
• KR2256.002	150 litres three phase vacuum waste collector - AISI 304 Stainlesssteel		2.488,00

OPTIONS			£
• 100	Fitted with single-phase vacuum unit		not available
•	Dual inlet (Ø 40 or 50 mm)		+ 45,00
•	Dual inlet (Ø 70 mm)		+ 54,00
•	Basket for vacuuming performances improvement		+ 421,00
•	Overheating safety relief valve		included
•	Silencer for painted version		included
•	Silencer for stainless steel version (.002)		included
•	Polyester bag instead of Nylon bag filter		---

THE ABOVE MENTIONED PRICES DO NOT INCLUDE ANY ACCESSORIES. For an effective and proper use according to your application requirements, please see our AP price list.  
 Versions available: L-M-H filtration (for hazardous powders vacuuming) certification