

TECHNICAL DATA				50 Hz	60 Hz
• Power	kW - HP			0,85 - 1,14	0,95 - 1,27
• Input voltages ¹⁾ Current settings available	V A			345Y ... 415Y 2,4Y ²⁾ 200D ... 240D 4,2D	380Y ... 480Y 2,3Y 220D ... 275D 4,0D
• Electrical cable length Electrical plug				6 meters Not supplied	
• ATEXmark				NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}				IP 55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O			2.000 1.600	2.400 1.600
• Maximum air flow	l/min - m ³ /h			2.400 - 144	2.916 - 175
• Acoustic level ^{d)}	dB (A)			63	66
• Dust Bin: capacity	l			114	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm			50 60	
• Dimensions: L x W x H Weight	mm kg			546 x 465 x 1.216 39	
• Packing size ⁵⁾ : L x W x H Weight	mm kg			720 x 720 x 1.400 45	
• Primary filter				Bag filter	
Surface area Diameter	cm ² - m ² mm			11.000 - 1,1 460	
Dust Class ^{e)} Media				Nylon L Polyester	

¹⁾ Other input voltages upon request

²⁾ Default factory setting

³⁾ Maximum vacuum in continuous run

⁴⁾ Marks proof wheels

⁵⁾ Standard packing size



Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69

BASIC VERSION PRICES			£
• KR1046	114 litres three phase vacuum waste collector - Painted		1.200,00
• KR1046.002	114 litres three phase vacuum waste collector - AISI 304 Stainlesssteel		1.479,00

OPTIONS			£
• 100	Fitted with single-phase vacuum unit		+ 294,00
•	Dual inlet (Ø 40 or 50 mm)		+ 45,00
•	Dual inlet (Ø 70 mm)		+ 54,00
•	Basket for vacuuming performances improvement		+ 273,00
•	Overheating safety relief valve		+ 120,00
•	Silencer for painted version		+ 128,00
•	Silencer for stainless steel version (.002)		+ 218,00
•	Polyester bag instead of Nylon bag filter		---

THE ABOVE MENTIONED PRICES DO NOT INCLUDE ANY ACCESSORIES. For an effective and proper use according to your application requirements, please see our AP price list.

Versions available: L-M-H filtration (for hazardous powders vacuuming) certification