

KOIL230

Three Phase

TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	3 - 4	3,45 - 4,7
• Input voltages ^{1) 2)} Current settings available	V A	360Y ... 440Y 6,7Y 200D ... 240D 11,6D	380Y ... 480Y 6,7Y 220D ... 275D 11,5D
• Electrical cable length Electrical plug type		9 meters 4 poles (5 poles upon request)	
• ATEX mark		NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	3.200 2.500	3.500 2.550
• Maximum air flow	l/min - m ³ /h	5.334 - 320	6.000 - 360
• Acoustic level ^{d)}	dB (A)	74	76
• Tank capacity:	l	200	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	50 150 - 150	
• Dimensions: L x W x H Weight	mm kg	1.150 x 560 x 1.600 160	
• Packing size ⁵⁾ : L x W x H Weight	mm kg	1.150 x 730 x 1.720 175	
• Expelling system (supplied with hose and gun)			
Pump power	kW - HP	0,53 - 0,7	
Pump capacity	l/min	200	
Hose length		3 meters	
• Swarf basket			
Capacity	l	28	
Diameter	mm	360	
Diameter swarf basket holes	mm	2	

1) ---

2) **Default factory setting: 400 V - 50 Hz**

3) Maximum vacuum in continuous run

4) Marks proof wheels with bearings

5) Packing size standard

Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

BASIC VERSION PRICES		£
• KOIL230	200 litres three phase vacuum cleaner	4.326,00

• 209175	Nylon filter 300 micron - Ø360	+ 61,00
• 209176	Nylon filter 100 micron - Ø360	+ 80,00
• 209177	Nylon filter 50 micron - Ø360	+ 91,00
• 209174	Nylon filter 300 micron - Ø460	not suitable
• 209178	Nylon filter 100 micron - Ø460	not suitable



THE ABOVE MENTIONED PRICES DO NOT INCLUDE ANY ACCESSORIES. For an effective and proper use according to your application requirements, please see our AP price list.

Versions available: • L-M-H filtration (for hazardous powders vacuuming) certification