

KOIL455T

Three Phase

TECHNICAL DATA		50 Hz	60 Hz
• Power	kW - HP	5,5 - 7,5	6,3 - 8,44
• Input voltages ^{1) 2)} Current settings available	V A	360Y ... 440Y 11,6Y 200D ... 240D 20,0D	380Y ... 480Y 11,6Y 220D ... 275D 20,0D
• Electrical cable length Electrical plug type		9 meters 4 poles (5 poles upon request)	
• ATEX mark		NO ATEX	
• Electric protection ^{a)} Insulation class ^{b)} Energetic class ^{c)}		IP55 F IE1	
• Maximum vacuum Optimum vacuum ³⁾	mmH ₂ O	5.100 4.450	5.100 4.300
• Maximum air flow	l/min - m ³ /h	5.334 - 320	6.500 - 390
• Acoustic level ^{d)}	dB (A)	75	76
• Tank capacity:	l	400	
• Diameters: material inlet wheels ⁴⁾ (front - rear)	mm	50 200 - 200	
• Dimensions: L x W x H Weight	mm kg	1.407 x 660 x 1.927 248	
• Packing size ⁵⁾ : L x W x H Weight	mm kg	1.500 x 800 x 1.900 263	
• Expelling system (supplied with hose and gun)			
Pump power	kW - HP	0,78 - 1	
Pump capacity	l/min	220	
Hose length		3 meters	
• Swarf basket			
Capacity	l	60	
Diameter	mm	460	
Diameter swarf basket holes	mm	2	

1) ---

2) Default factory setting: 400 V - 50 Hz

3) Maximum vacuum in continuous run

4) Marks proof wheels with bearings

5) Packing size standard



Normatives: a) IEC60529; b) IEC600085; c) IEC60034-2-1; d) EN60704-2-1; e) EN60335-2-69; f) EN1822

BASIC VERSION PRICES		£
• KOIL455T	400 litres three phase vacuum cleaner	9.198,00

OPTIONS		£
• 209175	Nylon filter 300 micron - Ø360	not suitable
• 209176	Nylon filter 100 micron - Ø360	not suitable
• 209177	Nylon filter 50 micron - Ø360	not suitable
• 209174	Nylon filter 300 micron - Ø460	+ 70,00
• 209178	Nylon filter 100 micron - Ø460	+ 109,00