

## TECHNICAL DATA

<b>• Input compressed air</b>		
Air flow required	nl/min	6.000
Pressure required	bar	4 ÷ 9
Antistatic hose	inner diameter	mm
	length	m
<b>• ATEXmark</b>		
NO ATEX		
<b>• Maximum vacuum</b>	mmH <sub>2</sub> O	4.500 <sup>1)</sup>
<b>• Maximum air flow</b>	l/min - m <sup>3</sup> /h	13.600 - 816 <sup>1)</sup>
<b>• Acoustic level</b> <sup>a)</sup>	dB (A)	78
<b>• Bin:</b>	capacity   wheels diameter	l   mm
<b>• Diameters:</b>	material inlet   wheels <sup>2)</sup> (front - rear)	mm
<b>• Dimensions:</b>	L x W x H   Weight	mm   kg
<b>• Size packing</b> <sup>3)</sup> :	L x W x H   Weight	mm   kg
<b>• Primary filter</b>		
Surface area   Diameter	cm <sup>2</sup> - m <sup>2</sup>   mm	35.000 - 3,5   560
Dust Class <sup>4)</sup> b)   Media <sup>5)</sup>		L   Polyester
Filter cleaning		Ergonomic manual shaker
<b>• Automatic filter cleaning - Optional</b>		
Surface area   Nominal output	cm <sup>2</sup> - m <sup>2</sup>   m <sup>3</sup> /h	Cartridges kit 94.800 - 9,48   3.410
Dust Class <sup>b)</sup>   Media		M   Antistatic polyester
Compressed air consumption   pressure	nl/min   bar	48   4 ÷ 6
<b>• Upstream absolute filter - Optional</b>		
Surface area   Nominal output	cm <sup>2</sup> - m <sup>2</sup>   m <sup>3</sup> /h	HEPA 14 105.000 - 10,5   600
Dust Class <sup>c)</sup>   Media		Glass fibre
Efficiency M.P.P.S. <sup>c)</sup> (with 0,18 µm particles)		99,995%

<sup>1)</sup> Measured at 6 bar

<sup>2)</sup> Marks proof wheels

<sup>3)</sup> Packing size standard

<sup>4)</sup> M class filters available upon request

<sup>5)</sup> Other materials available according to the material to be vacuumed

Normatives: a) EN60704-2-1; b) EN60335-2-69; c) EN1822

## BASIC VERSION PRICES

£

<b>• KC2</b>	90 litres compressed air driven vacuum cleaner	4.167,00
<b>• KC2.083</b>	<b>FOR LIQUIDS</b> - 90 litres compressed air driven vacuum cleaner	4.597,00

£

<b>• 001</b>	AISI 304 stainless steel dust bin (instead of the painted one)	+ 256,00
<b>• 002</b>	AISI 304 stainless steel dust bin and filtering chamber	+ 1.253,00
<b>• 005</b>	Upstream absolute filter (HEPA) with M dust class primary filter - version: painted   stainless steel	+ 976,00   + 1.319,00
<b>• 008</b>	Automatic reverse jet cartridge filtering system	upon request



THE ABOVE MENTIONED PRICES DO NOT INCLUDE ANY ACCESSORIES. For an effective and proper use according to your application requirements, please see our APO price list.

Versions available: **• L-M-H filtration** (for hazardous powders vacuuming) certification  
**• ATEX** certified machines